

Bringing the Benefits of Vertical Lifting Closer to the Patient

The Stature® vertical lift recognizes the true needs of the modern care environment. With an extensive lifting range and a choice of either loop or clip sling configurations, the Stature can cope with even the most demanding and technical of patient handling requirements.



POWERED CRADLE & SPREADER BAR OPTIONS



A powered positioning cradle is available to assist with patient repositioning as well as a standard loop-style spreader bar for use with loop style slings.

SCALE OPTION



Easy to use with intuitive controls, the digital scale is ideal for patient monitoring. Importantly, it does not compromise lifting height.

POWERED LEG ADJUSTMENT



The powered leg adjustment allows the caregiver to open and close the legs without bending, twisting or use of force.

EFFECTIVE LIFTING RANGE (ELR)



Designed to reach further across today's wide beds for safety and stability.

SWL

SAFE WORKING LOAD: 500 LB / 227 KG

SPECIFICATION		
Maximum Overall Length	54.7"	1390 mm
Minimum Overall Length	50.8"	1290 mm
Maximum Overall Height	83.8"	2130 mm
Minimum Overall Height	76.6"	1945 mm
Legs Open - External Width	53.5"	1360 mm
Legs Open - Internal Width	25.1"	1230 mm
Legs Closed - External Width	29.9"	760 mm
Legs Closed - Internal Width	25.1"	640 mm

WEIGHTS		
Mast, Base and Boom Assembly	142 lb	64.5 kg
Power Pack	6.6 lb	3 kg
Total	162 lb	73.5 kg
4-Point Positioning Cradle (manual)	13.2 lb	6 kg
4-Point Positioning Cradle (powered)	19.8 lb	9 kg

Specifications may vary due to manufacturing tolerances.

10 • 6190091 RevF • 001586 FLOOR LIFTS