

Defining Patient Handling for Over 70 Years





Table of Contents

THE HOYER® DIFFERENCE	4
Hoyer Familial Features	
Mobility Assessment & Lift Selection	
FLOOR LIFTS	9
Stature®	
Presence®	
Advance®	
Calibre®	
HPL450	
HPL700	
HPL402	
HML400	
STAND-AID LIFTS	19
Elevate®	
Journey®	
Hoyer Up	
SLINGS & ACCESSORIES	23
About Hoyer Slings	
Passive Slings	
Active Slings	
Spreader Bar & Cradles	
Accessories	
SAFE PATIENT HANDLING	38
ABOUT JOERNS HEALTHCARE	40



THE HOYER DIFFERENCE

Hoyer®, the trusted name in patient lifting

Hoyer lifts set the industry standard in patient handling, uniquely enhancing caregiver efficiency and safety while reducing injury risk. Backed by over 70 years of trusted performance, Hoyer ensures compliance, improves outcomes, and supports dignified care.



HOYER LIFTS CREATE THE STANDARD WHEN IT COMES TO USABILITY.

The direct correlation between safe patient handling principles and Hoyer's lift design ensures our products are simple, comfortable and, above all, safe to use. Careful attention to product design ensures correct ergonomic usage, protecting both the patient and the caregiver from injury at all times.

Safe Patient Handling Guidelines

- Get up close to the load
- Use a wide stable base
- Ensure a comfortable firm grasp
- Keep spine close to neutral
- Make sure movement is smooth

SUPPORTED BY EXPERT-DELIVERED JOERNS SOLUTIONS AND DESIGNED TO DRIVE BEST PRACTICE AND COMPLIANCE

Three Core Compliance Objectives

1. Integrate lifting policy and procedures
2. Education, training and mentoring
3. Improve outcomes and maximize ROI

Musculoskeletal disorders, specifically back injuries, have been an ongoing problem in the healthcare industry. With unparalleled experience in safe patient handling, Joerns Healthcare is available to support implementation of an SPH program customized to meet your unique needs.

Hoyer Familial Features*

STRAIGHT LINE DRIVE

Easy movement on long stretches

Stability minimizes damage to walls and doors during transport

Better movement in tight spaces



HOYER HANDLE (EXTRA WIDE AND TALL)

Large area provides caregivers the opportunity to position the lift more effectively for their comfort level

Protects electronic controls

Addresses comfortable grip aspect of safe patient handling principles

PUSH PAD

Addresses smooth movement of safe patient handling principles

Reduces lower back torque required for initial inertia

Endorsed by industry experts



BEST-IN-CLASS EFFECTIVE LIFTING RANGE**

Can work easily with the most critical of transfers

Minimum height ensures excellent off-the-floor transfers

Greater reach and spatial clearance

SMART MONITOR™

Displays and records vital lift utilization and service data

Drives usage compliance for Safe Patient Handling Programs

Service interval reminder helps prolong the life of the lift



*Familial features that may not be present on all lifts

**In-house study dated 2015

MOBILITY ASSESSMENT & LIFT SELECTION

This assessment is typically performed by a designated health professional or a team of health professionals. In addition, each patient will be assessed with regard to such factors as mental acuity, ability to comprehend instructions and cooperate in lifts and transfers, combativeness, weight, upper extremity strength, ability to bear weight, and specific medical conditions that may affect the selection of an appropriate means for lifting and transferring.

Patient Classification: This coding is consistent with activities of daily living (ADL) Self-Performance Codes for a patient's performance over all shifts during the last seven days.

INDEPENDENT Another person is not required for the activity No Helper	0 – TOTALLY INDEPENDENT (FIM* 6-7) Can ambulate normally without assistance; in unusual situations may need some limited assistance. Help or oversight may have been provided only one or two times in the last seven days.
DEPENDENT Another person is required for either supervision or physical assistance in order for the activity to be performed Help Needed	1 – SUPERVISION (FIM 5) Can ambulate normally without assistance; in unusual situations may need some limited assistance. Help or oversight may have been provided only one or two times in the last seven days. 2 – LIMITED ASSISTANCE (FIM 4) Highly involved in activity, able to pivot transfer, has considerable upper body strength, and bears some weight on legs. Can sit up well, but may need some assistance. Guided maneuvering of all limbs or other non-weight bearing assistance three or more times, or greater help provided one or two times during the last seven days. 3 – EXTENSIVE ASSISTANCE (FIM 3) Can perform part of the activity, usually can follow simple directions, may require tactile cueing, can bear some weight, sit up with assistance, has some upper body strength, may be able to pivot transfer. Over the last seven day period, help provided three or more times for weight-bearing transfers or may have required a total transfer.
COMPLETE DEPENDENCE Maximal or total assistance is required, or the activity is not performed	4 – TOTAL DEPENDENT (FIM 1-2) Cannot help at all with transfers; full staff assistance for activity during entire seven day period. Requires total transfer at all times.

By looking at the broad categories “dependent” (FIM scores 3, 4, and 5) and “complete dependence” (FIM scores 1 and 2), the FIM can assist in equipment needs identification, remembering that this tool is not designed for person-specific risk assessment.

MOBILITY ASSESSMENT & LIFT SELECTION

The table below indicates the type of equipment that may be appropriate in respect to each broad dependency category of a patient/person in order to ensure that safer handling practices can be facilitated. A person-specific risk assessment must be carried out in respect of those who require any assistance with movement/mobility.

Dependency Status	Floor or Overhead Lift (Passive)	Stand Aid Lift (Active)
INDEPENDENT	Unlikely to be required except in retrieval after fall or collapse	Unlikely to be required
DEPENDENT	May be required	Must be available
COMPLETE DEPENDENCE	Must be available	Unlikely to be required



Please Note: It is recommended that caregivers have immediate access to at least one mobile passive lift for use in the event of an emergency such as the retrieval of a patient who has fallen. A passive lift suitable for a very heavy person should also be accessible in facilities, and all caregivers should be aware of the system for accessing the lift as required. (For example, in the event of an unplanned admission of a very heavy patient).



Floor Lifts



STATURE



PRESENCE



ADVANCE



CALIBRE



HPL450



HPL700



HPL402



HML400



Bringing the Benefits of Vertical Lifting Closer to the Patient

The Stature® vertical lift recognizes the true needs of the modern care environment. With an extensive lifting range and a choice of either loop or clip sling configurations, the Stature can cope with even the most demanding and technical of patient handling requirements.

POWERED CRADLE & SPREADER BAR OPTIONS



A powered positioning cradle is available to assist with patient repositioning as well as a standard loop-style spreader bar for use with loop style slings.

SCALE OPTION



Easy to use with intuitive controls, the digital scale is ideal for patient monitoring. Importantly, it does not compromise lifting height.

POWERED LEG ADJUSTMENT



The powered leg adjustment allows the caregiver to open and close the legs without bending, twisting or use of force.

EFFECTIVE LIFTING RANGE (ELR)



Designed to reach further across today's wide beds for safety and stability.



SAFE WORKING LOAD: 500 LB / 227 KG

SPECIFICATION

Maximum Overall Length	54.7"	1390 mm
Minimum Overall Length	50.8"	1290 mm
Maximum Overall Height	83.8"	2130 mm
Minimum Overall Height	76.6"	1945 mm
Legs Open - External Width	53.5"	1360 mm
Legs Open - Internal Width	25.1"	1230 mm
Legs Closed - External Width	29.9"	760 mm
Legs Closed - Internal Width	25.1"	640 mm

WEIGHTS

Mast, Base and Boom Assembly	142 lb	64.5 kg
Power Pack	6.6 lb	3 kg
Total	162 lb	73.5 kg
4-Point Positioning Cradle (manual)	13.2 lb	6 kg
4-Point Positioning Cradle (powered)	19.8 lb	9 kg

Specifications may vary due to manufacturing tolerances.

Lightweight with a Best-in-Class Feature Set that Helps Drive Compliance

The robust and reliable Presence® lift is designed to handle almost any patient handling task. Its extensive lifting range enables off-the-floor transfers to high bed frame surfaces. With an impressive safe working load and numerous options to match its environment, the Presence lift is a truly flexible, all-round performer.

INTERCHANGEABLE CRADLE OPTIONS



Optional manual or powered cradles provides the caregiver with a wider choice of sling systems and effortless re-positioning.

SCALE OPTION



Easy to use with intuitive controls, the digital scale is NAWI Class III rated and ideal for patient monitoring. Importantly, it does not compromise lifting height.

POWERED LEG ADJUSTMENT



Powered leg adjustment allows the caregiver to open and close the legs without bending, twisting or use of force.



SAFE WORKING LOAD: 500 LB / 227 KG



HOYER SMART MONITOR

- ◊ Lift Cycle Counter
- ◊ Overload Protection
- ◊ Service Reminder
- ◊ Emergency

SPECIFICATION

Maximum Overall Length	57.5"	1460 mm
Minimum Overall Length	55.1"	1400 mm
Maximum Overall Height	81.3"	2065 mm
Minimum Overall Height	57.5"	1460 mm
Legs Open - External Width	45.3"	1150 mm
Legs Open - Internal Width	40.1"	1020 mm
Legs Closed - External Width	26.4"	670 mm
Legs Closed - Internal Width	21.7"	550 mm

WEIGHTS

Mast, Base and Boom Assembly	81.6 lb	37 kg
Power Pack	6.6 lb	3 kg
Total	88.2 lb	40 kg
Base Assembly	44.4 lb	20 kg
Mast & Boom Assembly (no battery)	37.5 lb	17 kg

Specifications may vary due to manufacturing tolerances.



Compact and Portable Folding Lift, When Space is at a Premium

The Advance® is a compact folding lift that can perform an outstanding range of transfers. Whether from the floor or onto a bed, the Advance copes with ease. Its unique triangular design also enables it to be folded for easy storage and transportation.



TRIANGULAR FOLDING DESIGN



Folding design requires no tools and allows the lift to stand unassisted when stored. It is also possible to transport the Advance in its folded configuration.

ERGONOMIC PUSH HANDLE



Large contoured handle promotes easier maneuverability and also provides protection for the control system from incidental damage.

ANGLED LEG DESIGN



Angled leg design provides stability while closed to navigate the room yet enables the widest possible opening to get closer to large chairs, bulky commodes, and wheelchairs.

TRANSPORTATION TRANSFERS



It is also possible to transport the Advance in its folded configuration making it great for transfers from car or van.



SAFE WORKING LOAD: 340 LB / 155 KG

SPECIFICATION

Maximum Overall Length	51.2"	1300 mm
Minimum Overall Length	49.2"	1250 mm
Maximum Overall Height	73.2"	1860 mm
Minimum Overall Height	53.5"	1360 mm
Legs Open - External Width	42.5"	1080 mm
Legs Open - Internal Width	39.4"	1000 mm
Legs Closed - External Width	26.4"	670 mm
Legs Closed - Internal Width	22.4"	570 mm

WEIGHTS

Mast, Base and Boom Assembly	63.7 lb	28.9 kg
Power Pack	6.2 lb	2.8 kg
Total	69.7 lb	31.7 kg
Base Assembly	32.8 lb	14.9 kg
Mast & Boom Assembly (no battery)	30.9 lb	14 kg

Specifications may vary due to manufacturing tolerances.

Bariatric Feature Set Developed with the Caregiver in Mind

The Calibre® is an ergonomically designed mobile patient lift for the safe lifting and handling of bariatric patients. Sturdy with a wealth of features that accommodate the custom needs of both the patient and care team, the Calibre, with an impressive safe working load of 850lb / 385 kg, meets the unique demands of the bariatric care environment.

WIDE PUSH HANDLE



The multi-point, right-sized push handle allows more than one caregiver to operate the lift, helping to avoid unnecessary strain and the potential for injury.

6-POINT POSITIONING CRADLE



The large, open cradle ensures greater spatial area and improved comfort for the patient. Great for working with patients of all sizes.

INTEGRATED SCALE



The Calibre is supplied with a low-profile digital, NAWI Class III scale. Easy-to-use with intuitive controls, the digital scale is ideal for patient monitoring.

POWERED LEG ADJUSTMENT



Powered leg adjustment allows the caregiver to open and close the legs without bending, twisting or using force.

TWIN FRONT CASTERS



Twin pivoting front casters are designed to give additional stability and maneuverability over uneven floor surfaces and room thresholds.



SAFE WORKING LOAD: 850 LB / 385 KG



HOYER SMART MONITOR

- ◊ Lift Cycle Counter
- ◊ Overload Protection
- ◊ Service Reminder
- ◊ Emergency

SPECIFICATION

Maximum Overall Length	70.7"	1795 mm
Minimum Overall Length	68.7"	1745 mm
Maximum Overall Height	88.6"	2250 mm
Minimum Overall Height	62.6"	1590 mm
Legs Open - External Width	55.1"	1400 mm
Legs Open - Internal Width	49.0"	1245 mm
Legs Closed - External Width	33.2"	845 mm
Legs Closed - Internal Width	26.8"	680 mm

WEIGHTS

Mast, Base and Boom Assembly	240.3 lb	109 kg
Power Pack	6.6 lb	3 kg
Total	246.9 lb	112 kg
6-Point Cradle	19.8 lb	9 kg

Specifications may vary due to manufacturing tolerances.



Best Value and Choice for More Patient Care Environments

The Hoyer® HPL450 series lift is a flexible mobile patient lift that is the perfect crossover product for both nursing and home care. Designed with upscale features, high lifting capacity, and lightweight design allowing the HPL450 to work well in almost all settings. The HPL450 provides additional value with optional electric leg versions.



OVERSIZED PUSH HANDLE



Optimally positioned and ergonomically designed for ease of maneuverability.

FOOT PEDAL LEG ADJUSTMENT



The ergonomically designed foot pedal is perfectly positioned to ensure the user's foot remains level during operation, helping to avoid risk of injury.

OPTIONAL POWERED BASE



Powered leg adjustment allows the caregiver to open and close the legs without bending, twisting or using force.

OPTIONAL SCALE



Simple to operate scale has a "zeroing out" feature that allows you to weigh the patient during transfer process, without including the weight of the sling.



SAFE WORKING LOAD: 450 LB / 204 KG

AVAILABLE CONFIGURATIONS

Powered w/Electric Leg	HPL450-EL
Powered w/ Manual Leg	HPL450-ML

SPECIFICATION

Maximum Overall Length	51.1"	1300 mm
Maximum Overall Height	79.8"	2027 mm
Minimum Overall Height	54.3"	1380 mm
Legs Open - External Width	48.4"	1250 mm
Legs Open - Internal Width	44.9"	1140 mm
Legs Closed - External Width	25.0"	660 mm
Legs Closed - Internal Width	22.8"	580 mm
Overall Height of Legs	3.9"	100 mm
Spreader Bar - Maximum Height	73.5"	1867 mm
Spreader Bar - Minimum Height	22.2"	565 mm

WEIGHTS

Mast, Powered Base and Boom	86.6 lb	39.3 kg
Power Pack	6.1 lb	2.8 kg
Powered Base Total	92.5 lb	42.0 kg
Mast, Manual Base and Boom	86.4 lb	39.2 kg
Manual Base Total	92.0 lb	41.7 kg

Specifications may vary due to manufacturing tolerances.

Best-in-Class Value Bariatric Lift with Technology to Promote User Compliance

The Hoyer® HPL700 is both sturdy and robust with a Safe Working Load of 700 lb. It is compatible with multiple spreader bars, allowing caregivers to use this one lift for patients considered bariatric and non-bariatric alike. This lift has been designed to be configured with or without a seamlessly integrated scale. The HPL700 is also equipped with unique Hoyer Smart Monitor technology that accurately records and displays vital lift utilization and service data.



INTERCHANGEABLE CRADLE OPTIONS



Compatible with multiple spreader bars, the interchangeable cradle options increase versatility, allowing caregivers to make the best choice for patients.

POWERED BASE



The powered base allows the legs to be opened and closed to enable access around armchairs, wheelchairs, and similar obstacles without bending or twisting.

ERGONOMIC PUSH HANDLE



Large contoured handle promotes easier maneuverability and provides protection for the control system from incidental damage.

OPTIONAL SCALE



Easy to use with intuitive controls, the digital scale is NAWI Class III rated and ideal for patient monitoring. Importantly, it does not compromise lifting height.



SAFE WORKING LOAD: 700 LB / 318 KG



HOYER SMART MONITOR

- ◊ Lift Cycle Counter
- ◊ Overload Protection
- ◊ Service Reminder
- ◊ Emergency

SPECIFICATION

Maximum Overall Length	56"	1423 mm
Minimum Overall Length	55"	1397 mm
Maximum Overall Height	81"	2058 mm
Minimum Overall Height	57.75"	1467 mm
Legs Open - External Width	46.25"	1175 mm
Legs Open - Internal Width	42.25"	1073 mm
Legs Closed - External Width	27.5"	699 mm
Legs Closed - Internal Width	23.5"	597 mm

WEIGHTS

Mast, Base and Boom Assembly	143.4 lb	65 kg
Power Pack	6.6 lb	3 kg
Total	150 lb	68 kg
Base Assembly	83 lb	38 kg
Mast & Boom Assembly (no battery)	40.4 lb	18 kg

Specifications may vary due to manufacturing tolerances.



Electric Version of Hoyer's Most Popular Product for Homecare

This lift is designed to be as comfortable as it is convenient, featuring a reverse-mounted actuator for increased knee clearance and ergonomic handle grips that reduce strain on the operator. The HPL402 features a mechanical downward release lever which allows patient moves to be performed without power, another important safety feature in the event of a power outage. The unit also features leg guards and caster bumpers to prevent damage to walls and furniture during transfers.



POWERED BOOM



Operating the powered patient lift is easy with its hand control and battery where a manual lift may be a challenge.

MANUAL LEG



Easily widen and narrow the base by pulling the adjustment handle back to unlock, right to widen and left to narrow the base.

LOW BASE



Low base needs only 5.5" clearance which makes it easy to roll under a bed or chair.



SAFE WORKING LOAD: 400 LB / 181 KG

SPECIFICATIONS

Overall Length	44.8"	1137 mm
Height of Boom at Highest Articulation	78"	1981 mm
Height of Boom at Lowest Articulation	30.5"	775 mm
Width of Base - Open	39.5"	1003 mm
Width of Base - Closed	24"	610 mm

WEIGHTS

Total	93 lb	42.2 kg
-------	-------	---------

Specifications may vary due to manufacturing tolerances.



The Most Popular Lift for Homecare

Our most popular Homecare lift, the HML400 Hoyer® Hydraulic Patient Lift has an ergonomically placed hydraulic pump for ease of use. The pump handle can be rotated from side to side allowing for operation from either side of the lift. This manual lift has an angular design with a non-sway cradle for extra stability. The “U” shaped base can be adjusted for easier access to wheelchairs and other furniture. The HML400 can be disassembled for easy storage and transportation.



“This Hoyer lift has made a huge difference for me and my caregivers. It makes things so much easier, especially when my husband is using it to get me situated for one of our movie nights or to put me to bed.”

Tasha Schuh, former Ms. Wheelchair USA (2012-2013)

DISASSEMBLES FOR STORAGE



The mast and base easily separate for storage or travel.

PUMP HANDLE ROTATION



Convenient rotating pump-handle allows for operation from both sides of the lift.

ADJUSTABLE “U” LEGS



When closed, U-legs facilitate maneuverability through doors and around corners. Expanded, legs allow for better positioning over commodes or chairs.



*Optional powered conversion kit available.



SAFE WORKING LOAD: 400 LB / 181 KG

SPECIFICATIONS

Overall Length	43.5"	1105 mm
Height of Boom at Highest Articulation	77"	1956 mm
Height of Boom at Lowest Articulation	28"	711 mm
Width of Base - Open	39.5"	1003 mm
Width of Base - Closed	24"	610 mm

WEIGHTS

Total	84 lb	38.1 kg
-------	-------	---------

Specifications may vary due to manufacturing tolerances.



Stand-Aid Lifts



ELEVATE



JOURNEY



HOYER UP



Heavy-Duty Stand Aid with an Extensive Feature Set Supporting Patient Monitoring and Rehabilitation

The Elevate is a high-performance active lift designed to improve the lifting experience for both the caregiver and the patient. It is both sturdy and compact with a maximum safe working load of 440 lb / 200 kgs. An optional digital scale allows the caregiver to precisely weigh a patient during the transfer process, saving time and avoiding unnecessary patient disruption.



REMOVABLE FOOT REST



The foot rest transforms the lift into a valuable restorative care aid, allowing the patient to fully stand and walk under close supervision.

POWERED LEG ADJUSTMENT



Powered leg adjustment allows the caregiver to open and close the legs without bending or twisting or use of force.

ADJUSTABLE KNEE PAD



Contoured, height adjustable knee pad offers high-level comfort and accommodates a range of patient sizes.

OPTIONAL CLASS III DIGITAL SCALE



Simple and intuitive controls allow precision weight monitoring during transfer, saving valuable time for caregivers.



SAFE WORKING LOAD: 440 LB / 200 KG



HOYER SMART MONITOR

- ◊ Lift Cycle Counter
- ◊ Overload Protection
- ◊ Service Reminder
- ◊ Emergency

SPECIFICATION

Maximum Overall Length	43.3"	1100 mm
Minimum Overall Length	41.0"	1040 mm
Maximum Overall Height	65.5"	1665 mm
Minimum Overall Height	48.4"	1230 mm
Legs Open - External Width	39.1"	995 mm
Legs Open - Internal Width	34.3"	870 mm
Legs Closed - External Width	24.8"	630 mm
Legs Closed - Internal Width	20.0"	510 mm

WEIGHTS

Mast, Base and Boom Assembly	127.3 lb	59 kg
Power Pack	6.6 lb	3 kg
Total	136.4 lb	62 kg
Base Assembly	40.7 lb	18.5 kg
Mast & Boom Assembly (no battery)	66 lb	30 kg

Specifications may vary due to manufacturing tolerances.

Versatile and Portable Stand Aid with Compact Footprint to Allow Navigation in Confined Spaces

The Journey is an ultra-compact, folding stand aid with best-in-class functionality. Both lightweight and nimble, it can be folded for easy storage and transportation. The unique adjustable cradle supports a wider range of patient heights and sizes, allowing your facility to have one lift that meets the need of many.



UNIQUE FOLDING DESIGN



Compact folding design enables transportation outside the confines of the home and allows the Journey to stand unassisted when stored.

ADJUSTABLE CRADLE



Unique adjustable cradle supports a range of patient heights and sizes and lends itself to transfers from lower surfaces.

ADJUSTABLE KNEE PAD



Contoured, height adjustable knee pad offers high level comfort and accommodates a large range of patient sizes.

REMOVABLE FOOT REST



The foot rest transforms the lift into a valuable restorative care aid, allowing the patient to fully stand and walk under close supervision.



SAFE WORKING LOAD: 340 LB / 155 KG



HOYER SMART MONITOR

- ◊ Lift Cycle Counter
- ◊ Overload Protection
- ◊ Service Reminder
- ◊ Emergency

SPECIFICATION

Maximum Overall Length	39.4"	1000 mm
Minimum Overall Length	36.8"	935 mm
Maximum Overall Height	63"	1600 mm
Minimum Overall Height	44.5"	1130 mm
Legs Open - External Width	38.2"	970 mm
Legs Open - Internal Width	34.5"	875 mm
Legs Closed - External Width	27"	685 mm
Legs Closed - Internal Width	22.2"	590 mm

WEIGHTS

Mast, Base and Boom Assembly	82.4 lb	37.4 kg
Power Pack	6.2 lb	2.8 kg
Total	88.6 lb	40.2 kg
Base Assembly	30.2 lb	13.7 kg
Mast & Boom Assembly (no battery)	42.3 lb	19.2 kg

Specifications may vary due to manufacturing tolerances.



Active Transfer Device for Use in All Settings

Easy to use and non-powered, Hoyer Up is a manual stand-aid and seated transfer device suitable for sling-free transfers with caregiver assistance.

Hoyer Up is designed for users who have some weight-bearing ability and can participate in the transfer promoting patient rehabilitation and functional independence. The Up simplifies care in all settings and helps maintain more activities of daily living.



UNIQUE MODULAR DESIGN




Simplifies inventory and transport with an efficient flat-pack design that requires no tools for assembly

SWING SEAT




Secure padded swing seat surface delivers comfort and stability. Seats fold flat against the side arms when not in use.

COMFORTABLE KNEE PAD



Enhances comfort and accommodates a larger range of patient sizes with a contoured, height adjustable knee pad.

ADJUSTABLE BASE



Increases patient care accessibility with a simple and robust mechanical foot pedal providing open/close functionality.



SAFE WORKING LOAD: 440 LB / 200 KG

SPECIFICATION

Overall Length	37.4"	950 mm
Overall width	24.8"	630 mm
Overall Height	43.3"	1100 mm
Legs Open - External Width	33.3"	845 mm
Legs Open - Internal Width	28.5"	725 mm
Legs Closed - External Width	23.6"	600 mm
Legs Closed - Internal Width	18.9"	480 mm
Leg Height	4.3"	110 mm
Casters	3" Front	4" Rear

WEIGHTS

Total*	72.8 lb	33 kg
--------	---------	-------

*Base 43 lbs, seat 21 lbs, mast 8.8 lbs

Specifications may vary due to manufacturing tolerances.

Slings & Accessories



PASSIVE SLINGS



ACTIVE SLINGS



SPREADER BAR AND CRADLES



ACCESSORIES


ABOUT HOYER® SLINGS

About Hoyer Slings


Hoyer has been designing and manufacturing slings, the all-important patient interface, for over 70 years. There is a Hoyer sling to meet every need. Fabric options are available, as well as specialty slings for hygiene, toileting, repositioning, turning, and gait training. Hoyer slings have many common attributes, which make them easier to train and easier to use.



COLOR CODED FOR SIZING with binding that provides clear recognized size information at a glance.



LABEL PROVIDES essential information about the sling including a unique serial number for traceability when completing inspection and audit records.



PADDING provides additional comfort and support to delicate areas and our webbing straps have covered ends to protect the patient's skin.



COLORLED LOOP STRAPS provide adjustment and the correct positioning angle for the 6-point spreader bar system.



POSITIONING HANDLES on our slings are carefully positioned to offer ease of handling.



DIGNITY STRAPS top the patient's legs from splaying while transferring, to maintain dignity.



CENTERLINE MARKERS aid the caregiver in the correct positioning of the sling, especially when inserting the sling before an off the bed or floor transfer.

IMPORTANT Remember to check the safe working load of the lift prior to lifting a patient as it may differ from that of the sling.

ABOUT HOYER® SLINGS

Sling Sizing

Hoyer slings are available in a range of sizes to accommodate variety in height, shape and weight of patients. Hoyer uses a simple color-coding system that ensures the size of your sling is instantly recognizable. The outer-edge binding of the sling is color coded-as shown. Hoyer's bariatric slings use a striped system to help differentiate from the standard range.



Size	Color	Recommended Weight Range									
		35 lb 15.9 kg	75 lb 34 kg	100 lb 45.4 kg	125 lb 56.7 kg	150 lb 68 kg	175 lb 79.4 kg	200 lb 90.7 kg	275 lb 124.7 kg	350 lb 158.8 kg	500 lb 227 kg
X Small	Brown										
Small	Red										
Medium	Yellow										
Large	Green										
X Large	Blue										

Hoyer Bariatric Slings

All Hoyer bariatric slings are rated to a safe working load of 850 lb /385 kgs. Due to the varying nature of bariatric patient shapes and sizes, it becomes increasingly difficult to provide a guide on sling size based on weight alone. Patients should be individually assessed to ascertain the correct size sling.

Size	Color	Color Example
M	Yellow with White Stripes	
L	Green with White Stripes	
XL	Red with White Stripes	
XXL	Yellow with White Stripes	
3XL	Green with White Stripes	
4XL	Blue with White Stripes	
5XL	Black with White Stripes	

IMPORTANT It is very important to use the correct sized sling and ensure it is properly fitted before attempting to lift. This will ensure the person being lifted feels safe, dignified and comfortable. It will also provide caregivers with confidence that they can achieve the transfer required and that the procedure will be executed in an effective and safe manner.



Hoyer slings can be customized outside of their standard specification to include adjustments to sizing. Should a standard sling size be deemed unsuitable, we can create a tailored sling to meet patient specific requirements. Contact Joerns Healthcare for more information.


ABOUT HOYER® SLINGS

Material Options



POLYESTER DISPOSABLE available on select models

- Developed for single patient use which helps reduce the risks of cross infection
- In order to maintain their integrity, these slings must not be laundered or exposed to water




POLYESTER / PADDED

- Strong, hard-wearing material is a consistent standard for Hoyer slings over the years
- Available in medium gray with selected sling models offered in alternative colors
- Padded option provides additional comfort and support to delicate areas



POLYESTER NET

- Quick drainage and drying properties are ideally suited to bathing and/or swimming pool environments
- Complementary to the polyester solid
- Net (or mesh) variant is also a common option through the Hoyer sling range



WOVEN SPACER

- Cushioned and breathable 3D woven spacer fabric
- Offers high air permeability and good drainage.
- Two-way stretch characteristics enable material to adapt to contours of the patient for higher levels of comfort and support

ABOUT HOYER® SLINGS

Spreader Bar and Cradle Options

The Hoyer lift range has the option of two sling attachment systems that provide the caregiver greater choice in selecting the most appropriate sling and cradle for a task. The Advance, Presence and Stature can be used with either the 6-point spreader bar or a 4-point positioning cradle. Both systems have their place. More importantly, this allows the caregiver to choose exactly the right sling for the patient and task in question.



6-POINT SPREADER BAR

6-POINT SPREADER BAR

The 6-point spreader bar uses slings with webbing loops that allow positioning adjustments to be made by selecting the different colored loops. The attachment straps at shoulder level determine the position of the back, ranging from upright to reclined. Similarly, the attachment straps at the legs determine the approximate degree of flexion at the hip, from around 90° to 45°.

The position achieved by adjusting the loops will depend upon the height and build of the patient. The rule of thumb is the shorter the shoulder straps, the more upright the patient will be.



4-POINT POSITIONING CRADLE
(powered version shown)

4-POINT POSITIONING CRADLES

The 4-point positioning cradle uses the safety clip system, and adjustment is made by rotating the cradle handle either down or up to obtain an upright or reclined position for the patient. Both manual and powered cradles are available.



INSERT



PULL/LOCK



SECURE



SAFE



BARIATRIC CRADLE

BARIATRIC CRADLE

The Bariatric Cradle is used when a large distance between the back and leg straps is appropriate, primarily for lifting and transferring bariatric patients. The Bariatric Cradle is compatible with the Calibre and HPL700 patient lifts and all Joerns bariatric slings. Additional flexibility is provided when a range of sling straps are used to position the patient in the sling. For example, extension straps can supplement the sling to open the hip angle of the patient still further for safer, more comfortable transfers.

ABOUT HOYER® SLINGS

Sling Selection and Risk Assessment

Selecting a sling for an individual patient involves more than simply measuring their size and deciding what the sling will be used for. To be sure that a sling meets specific requirements and is the most appropriate sling available, many further aspects need to be considered as part of the selection process. Some of these are discussed briefly here.

1

MOBILITY ASSESSMENT

It is necessary to establish a sling's compatibility with the lift or lifting system and the level of independence of the patient.

2

TYPE OF TRANSFER TASK

Determine the type of transfer task(s) that are desired, together with the frequency with which they will occur. This relates closely to the functional requirements of the sling (for example: a sling that is to be used for toileting may require a commode aperture).

3

SLING SUPPORT LEVELS


Different types of slings provide different levels of support for the patient being lifted. The support level is determined by the shape and structure of the fabric, with the main body of the sling providing support to the back and head (1) and the leg straps providing support to the thighs, hips and buttocks (2/3).



4

INFORMATION ABOUT THE CAREGIVER(S)

Experience and training of the caregiver(s) must be considered. Some slings are more complicated than others to fit and a caregiver may be reluctant to use a sling if the process of fitting it is too complex. The number of caregivers available to fit the sling as well as the total number of caregivers involved in a patient's care may also be important considerations.



5

INFORMATION ABOUT OTHER EQUIPMENT

Identify any associated equipment that is involved in a transfer, such as seating, beds, trolleys, toilets or therapy equipment to ascertain that the lift and sling will work effectively with these items.

ABOUT HOYER® SLINGS

Matching the Right Sling to the Task (Best Practice Guide)

To simplify the process of sling selection, we have developed a chart to help guide you in the appropriate use of each sling for a given task. There will, of course, be exceptions to this guide and Joerns Healthcare recommends that a full patient risk assessment is carried out prior to any transfer to determine individual requirements.

	SLING MODEL	EXAMPLE PATIENT LIFT	BED TO CHAIR	CHAIR TO CHAIR	COMMODOE/ TOILET TRANSFER	BATH/ SHOWER TRANSFER	FLOOR TO BED/ CHAIR	TURNING ASSIST	REHAB/ ASSISTED STANDING
PASSIVE / CEILING	Full Back	Loop	✓	✓	✓	✓ [†]	✓		
	Access	Loop	✓	✓	✓				
	Access with Head Support	Loop	✓	✓	✓				
	Quickfit	Loop	✓	✓	✓	✓ [†]	✓ [‡]		
	Quickfit Deluxe	Loop	✓	✓	✓	✓ [†]	✓		
	Long Seat	Loop	✓	✓	✓	✓ [†]	✓	✓	
	Long Seat with Commode*	Loop	✓	✓	✓	✓ [†]		✓	
	Hammock	Loop	✓	✓			✓	✓	
	U sling	Loop Classic	✓	✓	✓	✓ [†]	✓ [‡]		
	U sling with Head Support*	Loop Classic	✓	✓	✓	✓ [†]	✓		
	One Piece	Loop Classic	✓	✓	✓		✓		
	One Piece with Commode*	Loop Classic	✓	✓	✓		✓ [‡]		
	Repositioning	Loop	✓	✓	✓	✓ [†]	✓ [‡]	✓	
	Twin Turner	Loop						✓	
	Limb	Loop							✓
	Standing Harness	Loop							✓
	Comfort	Clip	✓	✓	✓	✓ [†]	✓		
	Comfort Access*	Clip	✓	✓	✓				
	Comfort Access Head Support	Clip	✓	✓	✓				
	Comfort Amputee	Clip	✓	✓	✓		✓	✓	
ACTIVE	Deluxe Stand-Aid	Loop Stand-Aid	✓	✓	✓				✓
	Deluxe Transport	Loop Stand-Aid	✓	✓	✓				✓
	Stand-Aid Clip*	Clip Stand-Aid	✓	✓	✓				✓

* Note added to sister sling

† Net version recommended

‡ Head support recommended

HOYER® SLINGS

Full Back Sling



SAFE WORKING LOAD:
600 lb / 272 kg



DEPENDENCY:
Complete Dependence
FIM 1-2



ATTACHMENT:
Loops
6-Point Spreader Bar



MATERIAL OPTIONS:
Padded Disposable
Mesh

This is a more specialized sling. It incorporates integral boned head support and padded leg pieces. Fitted correctly, this sling will give full protection for patients who go into extension, have involuntary movements or behavioral problems.

AREA	X SMALL (inch/mm)	SMALL (inch/mm)	MEDIUM (inch/mm)	LARGE (inch/mm)	X LARGE (inch/mm)
A	31.9 / 810	38.6 / 980	45.5 / 1180	53.5 / 1360	66.5 / 1690
B	20.5 / 520	20.9 / 530	25.2 / 640	28.3 / 720	30 / 890
C	40.6 / 1030	41.7 / 1060	46.9 / 1190	52.8 / 1340	64.2 / 1630
D	13 / 330	14.6 / 370	16.5 / 420	17.3 / 440	17.7 / 450



Access Padded Sling



SAFE WORKING LOAD:
500 lb / 227 kg



DEPENDENCY:
Complete Dependence
FIM 1-2




ATTACHMENT:
Loops
6-Point Spreader Bar



MATERIAL OPTIONS:
Padded

This sling is designed specifically to facilitate the toileting procedure by allowing the removal of clothing. It is NOT a general-purpose sling and will suit only 25% of patients. Patients must be in a sitting position to use this sling.

AREA	X SMALL (inch/mm)	SMALL (inch/mm)	MEDIUM (inch/mm)	LARGE (inch/mm)	X LARGE (inch/mm)
A	23.6 / 600	27.6 / 700	33.5 / 850	41.3 / 1050	51.1 / 1300
B	10.2 / 260	11 / 280	12.2 / 310	13 / 330	15.4 / 390
C	22.4 / 570	26 / 660	35 / 890	39.4 / 1000	44.7 / 1160
D	13.4 / 340	16.4 / 410	20.5 / 520	26.4 / 670	32.3 / 820
Chest Strap Adjustment (maximum length)					
MAX	39.8 / 1010	44.9 / 1140	49.2 / 1250	58.3 / 1480	72.8 / 1850



HOYER® SLINGS

Access Padded Sling with Head Support



SAFE WORKING LOAD:
500 lb / 227 kg



DEPENDENCY:
Complete Dependence
FIM 1-2



ATTACHMENT:
Loops
6-Point Spreader Bar



MATERIAL OPTIONS:
Padded

This sling is designed specifically to facilitate the toileting procedure by allowing the removal of clothing. It is NOT a general-purpose sling and will suit only 25% of patients. Patients must be in a sitting position to use this sling. Fitted with integrated head support for additional comfort.

AREA	SMALL (inch/mm)	MEDIUM (inch/mm)	LARGE (inch/mm)	X LARGE (inch/mm)
A	27.2 / 690	32.7 / 830	41.7 / 1060	49.6 / 1260
B	11.8 / 300	12.2 / 310	11 / 280	13.4 / 340
C	53.5 / 1360	61 / 1550	63 / 1600	73.2 / 1860
D	19.3 / 490	21.3 / 540	23.2 / 590	26.4 / 670



Quickfit Sling



SAFE WORKING LOAD:
500 lb / 227 kg



DEPENDENCY:
Complete Dependence
FIM 1-2



ATTACHMENT:
Loops
6-Point Spreader Bar



MATERIAL OPTIONS:
Padded
Mesh

This sling is an easy-to-fit, general-purpose sling designed to suit approximately 85% of patients. It is available with head support and can be felt lined for additional comfort.

AREA	X SMALL* (inch/mm)	SMALL (inch/mm)	MEDIUM (inch/mm)	LARGE (inch/mm)	X LARGE* (inch/mm)
A	22.0 / 559	28.7 / 730	35.4 / 900	43.7 / 1110	52.5 / 1334
B	18 / 457	22 / 560	24.4 / 620	27.6 / 700	34 / 864
C	34.0 / 864	44.1 / 1120	47.6 / 1210	55.1 / 1400	68.5 / 1740

* Applies to padded version only



HOYER® SLINGS

Quickfit Deluxe Sling



SAFE WORKING LOAD:
500 lb / 227 kg



DEPENDENCY:
Complete Dependence
FIM 1-2



ATTACHMENT:
Loops
6-Point Spreader Bar



MATERIAL OPTIONS:
Padded Polyester
Mesh

The Quickfit Deluxe sling is suitable for 95% of patients. It is available with head support and can be used for amputees following a careful assessment.

AREA	X SMALL (inch/mm)	SMALL (inch/mm)	MEDIUM (inch/mm)	LARGE (inch/mm)	X LARGE (inch/mm)
A	21.5 / 546	30.3 / 770	35 / 890	41 / 1041	52 / 1320
B	18.75 / 476	24.8 / 630	30.3 / 770	33.5 / 850	41.3 / 1049
C	27.75 / 705	36.2 / 920	44.1 / 1120	47.5 / 1206	59.3 / 1506

* XS only applies to polyester, XL only applies to mesh and polyester



Long Seat Sling



SAFE WORKING LOAD:
500 lb / 227 kg



DEPENDENCY:
Complete Dependence
FIM 1-2



ATTACHMENT:
Loops
6-Point Spreader Bar



MATERIAL OPTIONS:
Polyester
Mesh

The Long Seat sling is designed for amputees, but it is also suitable for other patients who have to remain in the sling for an extended period, i.e. during bed making when bathing.

AREA	SMALL (inch/mm)	MEDIUM (inch/mm)	LARGE (inch/mm)	X LARGE (inch/mm)
A	23.2 / 590	27.1 / 690	28.7 / 730	30.3 / 768
B	40.2 / 1020	42.0 / 1067	46.5 / 1181	49.8 / 1263

* XL applies to polyester



HOYER® SLINGS

Bariatric Hammock Sling



SAFE WORKING LOAD:
850 lb / 385 kg



DEPENDENCY:
Complete Dependence
FIM 1-2




ATTACHMENT:
Loops
6-Point Spreader Bar



MATERIAL OPTIONS:
Spacer

This is a more specialized sling. It incorporates integral boned head support and padded leg pieces. Fitted correctly, this sling will give full protection for patients who go into extension, have involuntary movements or behavioral problems.

AREA	X LARGE (inch/mm)	2X LARGE (inch/mm)	3X LARGE (inch/mm)	4X LARGE (inch/mm)	5X LARGE (inch/mm)
A	39.8 / 1010	44.1 / 1120	50 / 1270	58.3 / 1480	68.9 / 1750
B	64.2 / 1630	64.2 / 1630	64.6 / 1640	64.6 / 1640	63.8 / 1620
C	11.4 / 290	12.2 / 310	12.2 / 310	12.2 / 310	12.2 / 310



U Sling (with/without Head Support)



SAFE WORKING LOAD:
500 lb / 227 kg



DEPENDENCY:
Complete Dependence
FIM 1-2



ATTACHMENT:
Loops
6-Point Spreader Bar



MATERIAL OPTIONS:
Padded

The Universal sling is an easy fit general purpose sling designed to suit approximately 85% of patients. It is available with or without head support for additional comfort.

AREA	SMALL (inch/mm)	MEDIUM (inch/mm)	LARGE (inch/mm)	X LARGE (inch/mm)
A	33.5 / 851	39.5 / 1003	47 / 1194	51 / 1295
B	32 / 813	38 / 965	42 / 1067	61 / 1549



HOYER® SLINGS

One Piece Sling (also Commode version)


SAFE WORKING LOAD:

500 lb / 227 kg


DEPENDENCY:

 Complete Dependence
FIM 1-2

ATTACHMENT:

 Loops
6-Point Spreader Bar

MATERIAL OPTIONS:

Polyester



This sling is designed for amputees, but it is also suitable for other patients who have to remain in the sling for an extended period, i.e. during bed making when bathing.

AREA	SMALL (inch/mm)	MEDIUM (inch/mm)	LARGE (inch/mm)	X LARGE (inch/mm)
A	26 / 813	32 / 660	35.5 / 902	39.5 / 1003
B	32 / 660	38.5 / 978	42.5 / 1080	47.0 / 1194

* XL applies to Commode version



Limb Sling



The Limb sling is designed to assist with the elevation and support of a patient's arm or leg to facilitate examination, care or treatment of wounds. Available with multi loop configuration for adjustability.

Twin Turner Sling



The Twin Turner sling is used to assist in turning or "log rolling" a patient as well as maintaining them in position for purposes of hygiene or other care tasks. It is designed to be easily placed and removed as well as providing more access to the patient to provide skin care.

Repositioning Sling



The Repositioning Sling is designed to simplify patient repositioning, turning, or transferring. Crafted from breathable, flexible mesh for durability and

comfort, it is typically placed under the top sheet for ease of use.

Slidesheets



The ultra-low friction of a Slidesheet significantly reduces resistance, making it possible to carry out a variety of basic patient handling tasks with ease and efficiency, all without the need to physically lift the patient, thereby minimizing strain on caregivers and enhancing patient comfort.

HOYER® SLINGS

Standing Harness Sling



SAFE WORKING LOAD:
500 lb / 227 kg



DEPENDENCY:
Complete Dependence
FIM 3-4




ATTACHMENT:
Loops
6-Point Spreader Bar



MATERIAL OPTIONS:
Polyester

The Standing Harness is a versatile sling used to assist with standing, walking or toileting. The Standing Harness is not a general-purpose sling and requires the patient to be able to partially bear weight.

AREA	X SMALL (inch/mm)	SMALL (inch/mm)	MEDIUM (inch/mm)	LARGE (inch/mm)
A (min)	11.8 / 300	15.3 / 390	21.2 / 540	34.4 / 875
A (max)	16.1 / 410	23.2 / 590	29.1 / 740	42.3 / 1075
B	4.3 / 110	4.3 / 110	6.3 / 160	6.3 / 160



Comfort Sling



SAFE WORKING LOAD:
500 lb / 227 kg



DEPENDENCY:
Complete Dependence
FIM 1-2



ATTACHMENT:
Clips
4-Point Cradle



MATERIAL OPTIONS:
Padded Disposable
Mesh

This sling allows correct positioning to be made via the 4 point cradle. The Securi3 clip system ensures no inadvertent detachment of the sling from the cradle. It is ideal for patients who go into extension, have involuntary movements or behavioral problems.

AREA	X SMALL (inch/mm)	SMALL (inch/mm)	MEDIUM (inch/mm)	LARGE (inch/mm)	X LARGE (inch/mm)
A	31.9 / 810	38.6 / 980	46.5 / 1180	53.5 / 1360	66.5 / 1690
B	33.9 / 860	35 / 890	41.7 / 1060	45.7 / 1160	52.8 / 1340
C	51.6 / 1310	53.9 / 1370	62.2 / 1580	69.3 / 1760	82.3 / 2090



HOYER® SLINGS

Comfort Access Padded Sling with Head Support



SAFE WORKING LOAD:
500 lb / 227 kg



DEPENDENCY:
Complete Dependence
FIM 1-2



ATTACHMENT:
Clips
4-Point Cradle



MATERIAL OPTIONS:
Padded

Used with a 4-point cradle, this sling is designed specifically to facilitate the toileting procedure by allowing the removal of clothing. It is NOT a general-purpose sling and will suit only 25% of patients. Patients must be in a sitting position to use this sling. Fitted with integrated head support for additional comfort

AREA	SMALL (inch/mm)	MEDIUM (inch/mm)	LARGE (inch/mm)	X LARGE (inch/mm)
A	27.2 / 690	32.7 / 830	41.7 / 1060	49.6 / 1260
B	11.8 / 300	12.2 / 310	11 / 280	13.4 / 340
C	53.5 / 1360	61 / 1550	63 / 1600	73.2 / 1860
D	19.3 / 490	21.3 / 540	23.2 / 590	26.4 / 670

*Also available without head support



Comfort Amputee Sling



SAFE WORKING LOAD:
500 lb / 227 kg



DEPENDENCY:
Complete Dependence
FIM 1-2




ATTACHMENT:
Clips
4-Point Cradle



MATERIAL OPTIONS:
Polyester

The Amputee Comfort sling is designed for amputees but is also suitable for other patients who have to remain in the sling for an extended period, such as for bed making or bathing. An amputee spreader bar is required for use with the amputee sling.

AREA	SMALL (inch/mm)	MEDIUM (inch/mm)	LARGE (inch/mm)
A	38.2 / 970	45.7 / 1161	51.2 / 1300
B	30.5 / 775	34.8 / 884	39 / 991
C	15.6 / 396	16.5 / 419	17.3 / 439



HOYER® SLINGS

Deluxe Stand-Aid Sling



SAFE WORKING LOAD:
440 lb / 200 kg



DEPENDENCY:
Dependent
FIM 3-4




ATTACHMENT:
Loops
6-Point Spreader Bar



MATERIAL OPTIONS:
Polyester
Disposable

The Standing sling is suitable for those patients who have a greater degree of weight bearing ability. It allows good access for toileting and is easy to fit, providing quick and effective transfers. The adjustable waist strap and the non-slip back pad ensures a comfortable transfer.

AREA	SMALL (inch/mm)	MEDIUM (inch/mm)	LARGE (inch/mm)
A	28.3 / 720	32.7 / 830	42.1 / 1070
B	12.2 / 310	13 / 330	13.4 / 340
C	29.1 / 740	35.4 / 900	48 / 1220
Chest Strap Adjustment (maximum length)			
MAX	40.1 / 1020	53.5 / 1360	61.4 / 1560



*Also available in clip version

Deluxe Transport Sling



SAFE WORKING LOAD:
440 lb / 200 kg



DEPENDENCY:
Dependent
FIM 2-4




ATTACHMENT:
Loops
6-Point Spreader Bar



MATERIAL OPTIONS:
Polyester

This sling is suitable for those patients with a moderate degree of weight bearing ability. It is easy to fit, allowing quick and effective transfers. The adjustable waist strap and the non-slip back pad ensures a comfortable transfer.

AREA	SMALL (inch/mm)	MEDIUM (inch/mm)	LARGE (inch/mm)
A	26.4 / 670	33.1 / 840	43.3 / 1100
B	11.4 / 290	13.4 / 340	15.7 / 400
C	33.9 / 860	39.8 / 1010	41.7 / 1060
Chest Strap Adjustment (maximum length)			
MAX	40.9 / 1040	51.6 / 1310	65 / 1650



WHY SAFE PATIENT HANDLING MATTERS

PROTECTING PATIENTS AND CAREGIVERS

Musculoskeletal disorders (MSDs) are a major concern in healthcare. Nursing assistants experience MSDs at a rate 6x higher than other industries¹. Nurses may lift up to 1.8 tons in a single shift². 50% of nurses report back pain after repositioning tasks³.



THE COST OF INJURY

Injuries impact more than just health: direct costs include medical expenses and compensation, while indirect costs include staff replacement, training, morale, supervision time, and potential patient harm⁵.

Average **cost per**
back **injury** claim:
\$24,000⁴

SAFE PATIENT HANDLING (SPH) PROGRAM SUCCESS

A pilot program in two long-term care facilities showed dramatic improvements. Facility A reduced costs from \$156,210 to \$0, and Facility B from \$65,000 to \$2,635. Overall, there was a 47% reduction in total worker compensation claims⁶.

0

LOST WORKDAYS
AFTER SPH PROGRAM
IMPLEMENTATION

BEYOND LIFTS: A HOLISTIC APPROACH

SPH isn't just about Hoyer lifts. Effective programs include bed frames with integrated safety features, therapeutic support surfaces, repositioning aids, and staff education².



WORKS CITED

- [1] Bureau of Labor Statistics. (2016). Healthcare. Retrieved from <https://www.bls.gov/ooh/healthcare/nursing-assistants.htm#tab-3>
- [2] Nelson, A. B. (2004). Evidence-based practices for safe patient handling and movement. *Online Journal of Issues in Nursing*, 9(3).
- [3] Smedley, J. E. (1995). Manual handling activities and risk of low back pain in nurses. *Occupational and Environmental Medicine*, 52, 160–165.
- [4] IRIS. (2025). The back breaking cost of back pain in the US. Retrieved from <https://www.irisglobal.com/blog/the-back-breaking-cost-of-back-pain-in-the-us/>
- [5] Lackey, L. R. (2010). Low back pain, nurses' nemesis. *Nursing Continuing Education*, 28–33.
- [6] U.S. Department of Health and Human Services. (2010, September). Findings from the 2008 national sample of registered nurses. Retrieved from https://campaignforaction.org/wp-content/uploads/2016/06/RN_Population.pdf

PROMOTING MOBILITY THROUGH EQUIPMENT & DESIGN

Every extra day in bed = 3 more days of rehab



50%
FALLS IN LONG-TERM CARE OCCUR AT OR NEAR THE BED

Low beds aren't just for **fall prevention** - they **support mobility** too!

EARLY MOBILITY = BETTER OUTCOMES

Implementing early mobility programs leads to decreased hospital-acquired conditions, length of stay, falls and injuries, and increased patient and staff satisfaction. Functional status improves with mobility^{7, 8, 9}.

CASE STUDY HIGHLIGHTS

Vent Unit: 81% of patients in early mobility program showed improved outcomes⁷. Post-op Recovery: 70% reduction in hospital stay with in-room rehab⁹. Abdominal Surgery: Fewer complications and readmissions with enforced mobility⁸.

BED SYSTEMS THAT SUPPORT MOBILITY

The bed system is central to safe patient handling. Key features include auto-transfer height, assist handles, and firm perimeter surfaces to prevent sliding during transfers^{10, 11}.

DESIGN FOR DIGNITY AND SAFETY

Getting in and out of bed is essential for dignity and quality of life. Integrated bed features reduce strain on caregivers and promote independence for residents^{12, 13}.

WORKS CITED

- [7] Gosseling, L. (2014). Nurse-driven early mobilization program outcomes. *Journal of Critical Care*.
- [8] Van der Leeden, M., & Huijsmans, R. (2016). Early enforced mobility post abdominal surgery. *Journal of Rehabilitation Medicine*.
- [9] Tayrose, G. (2013). Rapid recovery in post-operative care. *Orthopedic Nursing Journal*.
- [10] Thapa, P. B. (1996). Falls in long-term care. *Journal of the American Geriatrics Society*.
- [11] Tideiksaar, R. (2010). Bedside falls in long-term care. *Journal of Gerontological Nursing*.
- [12] Nurmi, I. (1996). Fall risk in institutionalized elderly. *Scandinavian Journal of Public Health*.
- [13] Rubenstein, L. Z. (1994). Epidemiology of falls in the elderly. *Clinical Geriatric Medicine*.

A vertically integrated manufacturer since 1889, Joerns tenure and experience are unmatched in the delivery of long-term care equipment sales and support services. It is our mission to make affordable, accessible solutions available to restorative care providers and their patients that are effective, reliable, and safe.

WHO WE SERVE



1889 ESTABLISHED	N.A. BASED & OWNED	200K ft ² MANUFACTURING FACILITY	50K UNITS PRODUCED/YR	100K ft ² DISTRIBUTION CENTER
---------------------	-----------------------	--	--------------------------	---

INNOVATIVE PRODUCTS

 Joerns UltraCare®

 Joerns Hoyer®

 Joerns Dolphin®

 Joerns P.R.O. Matt®



Our Values

At Joerns, we are **OTHER-CENTERED** (You-focused)- we think and act on behalf of others over ourselves. We are **HUNGRY** - ambitious, resourceful, and never satisfied; we constantly pursue better. We are **HUMBLE** - confident in our abilities but equally committed to constant growth and improvement. We are **INTELLIGENT** - adding value by being attuned emotionally, fully engaged intellectually, and bringing all our experience to every interaction.



Accredited by The Joint Commission



US Customer Care
General: 800.826.0270

Customer Experience and Collaboration Center
2430 Whitehall Park Drive
Suite 700
Charlotte, NC 28273

2100 Design Road, Suite 100
Arlington, TX 76014

www.Joerns.com

Canada Customer Care
866.546.1151

Canada Office
35 Consortium Court
London, ON Canada
N6E 2S8

Netherlands and EU
+31 088 2080 200
Zeilschip 26, 3991 CT Houten,
Nederland